

Project Documentation Gebäude-Dokumentation

Abstract | Zusammenfassung



Betances Residence, 445 East 142nd Street, Bronx, NY

Data of building | Gebäudedaten

Year of construction Baujahr	2019	Space heating Heizwärmebedarf	9 kWh/(m²a)
U-value external wall U-Wert Außenwand	0.196 W/(m²K)		
U-value basement U-Wert Kellerdecke	0.294 W/(m²K)	Primary Energy Renewable (PER) Erneuerbare Primärenergie (PER)	87 kWh/(m²a)
U-value roof U-Wert Dach	0.091 W/(m²K)	Generation of renewable Energy Erzeugung erneuerb. Energie	See below
U-value window U-Wert Fenster	1.04 W/(m²K)	Non-renewable Primary Energy (PE) Nicht erneuerbare Primärenergie (PE)	119 kWh/(m²a)
Heat recovery Wärmerückgewinnung	84 %	Pressurization test n_{50} Drucktest n_{50}	0.5 h ⁻¹
Special features Besonderheiten	The ground floor is mixed use with healthcare offices, community room, library, computer room, fitness center, kindergarten and private outdoor space. The rooftop includes a photovoltaic array producing 35,417 kWh/yr.		

Betances Residence

Betances was developed by Breaking Ground, New York's largest provider of street outreach and supportive housing. It is the group's first Passive House residence, which will house and support homeless and low income seniors. The building is located between East 142nd Street and East 143rd Street in the Mott Haven neighborhood of the Bronx in New York City. The 8 story, 152-unit residence will dedicate 25% of units to New York City Housing Authority (NYCHA) seniors, 45 units to homeless seniors, and remaining units to seniors with incomes of less than 50% of the area median income.

The project includes active design principles, outdoor garden spaces, accessible accommodations, as well as Social Services support to refer tenants to medical care. The building is organized into two residential towers, with a variety of shared spaces at the ground floor connecting the two towers that promote mental and physical well-being, independence and social connectedness for the residents. These shared spaces and services include: on-site medical and psychiatric care, a garden, a library, a multi-purpose room, a computer room, a fitness room, bicycle storage and laundry as well as a separate Community Facility for a community-based non-profit tenant.

The design and construction of Betances V provides a superior living environment for residents. The high mass construction, continuous thermal envelope, and high-performance windows significantly reduces noise from outdoors. This translates to a quieter, more peaceful apartment setting. In addition, the thermal envelope and windows, coupled with the heating/cooling system allows residents to set and maintain their own consistent, comfortable temperature. Cold-surfaces and drafts have been eliminated with high-performance windows and thorough air-sealing and compartmentalization. The ERVs deliver a continuous flow of fresh, filtered air from outdoors and remove stale air from each apartment, resulting in excellent indoor air quality.

Responsible project participants | Verantwortliche Projektbeteiligte

Architect Entwurfsverfasser	COOKFOX Architects 250 W 57th St 10107 New York , United States of America
Client	BREAKING GROUND 505 8th Ave 10018 New York, United States of America
Building systems Haustechnik	DAGHER ENGINEERING 29 Broadway 10006 New York, United States of America
Structural engineering Baustatik	WSP 1 Pennsylvania Plaza New York, NY 10119, United States of America
Building physics Bauphysik	STEVEN WINTER ASSOCIATES 307 Seventh Avenue New York, NY 10001, United States of America
Passive House project planning Passivhaus-Projektierung	STEVEN WINTER ASSOCIATES 307 Seventh Avenue New York, NY 10001, United States of America
Construction management Bauleitung	MONADNOCK CONSTRUCTION 155 3rd St Brooklyn, NY 11231, United States of America

Certifying body Zertifizierungsstelle

PASSIVE HOUSE ACADEMY
334 Douglass, Brooklyn, NY 11217, United States of America

Certification ID Zertifizierungs ID

6336

Project-ID (www.passivehouse-database.org)
Projekt-ID (www.passivhausprojekte.de)

Author of project documentation Verfasser der Gebäude-Dokumentation

Thomas Moore
STEVEN WINTER ASSOCIATES

Date
Datum

Signature
Unterschrift

15.07.2022




1. Exterior Photos | Ansichtsfotos

Street View



© COOKFOX

Entry View




Courtyard View




2. Interior Photos | Innenfoto exemplarisch

Interior Circulation




© COOKFOX

Typical Apartment




3. Building Sections | Schnittzeichnung

BETANCES SENIOR HOUSING PASSIVE HOUSE FEATURES




4. Floor Plans | Grundrisse


First Floor Plan



Typical Floor Plan



5. Floor Construction | Konstruktion der Bodenplatte





TYPICAL WALL BASE AT FOOTING

NOT TO SCALE

Assembly no.	Building assembly description		Heat transmission resistance [m ² K/W]			Interior insulation?
04ud	Slab					
Orientation of building element		3-Floor	interior Rsi	0.13		
Adjacent to		2-Ground	exterior Rse	0.00		
Area section 1	λ [W/(mK)]	Area section 2 (optional)	λ [W/(mK)]	Area section 3 (optional)	λ [W/(mK)]	Thickness [mm]
Concrete Reinforced	1.442		0.000		0.000	203
XPS	0.029		0.000		0.000	51
	0.000		0.000		0.000	0
	0.000		0.000		0.000	0
	0.000		0.000		0.000	0
	0.000		0.000		0.000	0
	0.000		0.000		0.000	0
	0.000		0.000		0.000	0
Percentage of sec. 1		Percentage of sec. 2		Percentage of sec. 3		Total
100%		0.0%		0.0%		25.4 cm
U-value supplement		0.00 W/(m ² K)		U-value:		0.492 W/(m ² K)

6. Exterior Wall Construction | Konstruktion der Außenwände






TYPICAL METAL PANEL WALL ASSEMBLY

NOT TO SCALE

Assembly no.		Building assembly description			
01ud		WT-1.0_Metal Rain Screen_6" Mineral Wool EXT			
		Heat transmission resistance [m ² K/W]			
Orientation of building element		2-Wall	interior R _{si}	0.13	
Adjacent to		1-Outdoor air	exterior R _{se}	0.04	
Area section 1	λ [W/(mK)]	Area section 2 (optional)	λ [W/(mK)]	Area section 3 (optional)	λ [W/(mK)]
Heat 3 Calculation (reference "WT1.0 HEAT3 Calculation")	0.005		0.000		0.000
	0.000		0.000		0.000
Percentage of sec. 1		Percentage of sec. 2		Percentage of sec. 3	
100%		0.0%		0.0%	
U-value supplement		0.00	W/(m ² K)		
		U-value:		0.196	W/(m ² K)




TYPICAL BRICK VENEER WALL ASSEMBLY

NOT TO SCALE

Assembly no.		Building assembly description			
02ud		WT-2.0_Brick w/ GALV Ties_3" KoolTherm K8 EXT			
Heat transmission resistance [m²K/W]					
Orientation of building element		2-Wall		interior Rsi	0.13
Adjacent to		1-Outdoor air		exterior Rse:	0.04
Area section 1	λ [W/(mK)]	Area section 2 (optional)	λ [W/(mK)]	Area section 3 (optional)	λ [W/(mK)]
Heat 3 Calculation (reference "WT2.0 HEAT3 Calculation")	0.005		0.000		0.000
	0.000		0.000		0.000
Percentage of sec. 1		Percentage of sec. 2		Percentage of sec. 3	
100%		0.0%		0.0%	
U-value supplement		0.00 W/(m²K)		U-value: 0.187 W/(m²K)	


7. Roof Construction | Konstruktion des Daches




Section at Parapet/Roof Coping, Metal Rainscreen
Not to Scale

Assembly no. 06ud		Building assembly description Roof		Interior insulation? <input type="checkbox"/>		
Orientation of building element: 2-Wall		Heat transmission resistance [m ² K/W]				
Adjacent to: 1-Outdoor air		interior Rsi: 0.13		exterior Rse: 0.04		
Area section 1	λ [W/(mK)]	Area section 2 (optional)	λ [W/(mK)]	Area section 3 (optional)	λ [W/(mK)]	Thickness [mm]
Concrete Reinforced	1.442		0.000		0.000	305
Polyiso Insulation (10" min)	0.024		0.000		0.000	254
	0.000		0.000		0.000	0
	0.000		0.000		0.000	0
	0.000		0.000		0.000	0
	0.000		0.000		0.000	0
	0.000		0.000		0.000	0
	0.000		0.000		0.000	0
	0.000		0.000		0.000	0
Percentage of sec. 1: 100%		Percentage of sec. 2: 0.0%		Percentage of sec. 3: 0.0%		Total: 55.9 cm
U-value supplement: 0.00 W/(m ² K)		U-value: 0.091 W/(m ² K)				


8. Windows and Window Installation | Fenster und Fenster-Einbau



Section at Window, Metal Rainscreen
Not to Scale




Window Frame Description:	Schüco Living 82 MD TopAlu
Manufacturer:	Schüco
Frame u-value:	0.96 W/(m ² K)
Glazing	SGG CLIMATOP 6 18 ARGON 90 4 18 ARGON 90 4 ; PLANITHERM ONE F2, PLANITHERM ONE F5
Glass u-value:	0.48 W/(m ² K)
SHGC	33%



9. Airtight Building Envelope | Beschreibung der luftdichten Hülle

Photo 1:



Whole Building:

- Net Int. Volume: **812,551 ft³**
- Treated Floor Area: 79,920 ft²

TOTAL: Average @ 50Pa: **6123**

✓ The calculated 95% Confidence Interval is less than 8%; final CI was 1%

✓ The result meets the 0.6 ACH50 requirement; **final ACH was 0.45 ACH50**

✓ Determination = PASS

10. Ventilation Equipment | Lüftungsgerät

The project utilized highly efficient rotary heat exchangers.

"A rotary heat exchanger consists of an aluminum wheel with numerous small air passages. Energy is transferred between the supply air and extract air or vice versa when the wheel rotates. This is the most energy efficient heat recovery method with a temperature efficiency that always exceeds 80%."



Manufacturer / Model	Swegon Gold RX
Overall Effective Heat Recovery Efficiency	84 %
Overall Spec Input Power	0.37 Wh/m ³

11. Short Documentation of PHPP-Results (verification sheet) | PHPP-Ergebnisse

Passive House Verification



Building:	BETANCES_V		
Street:	455 East 142nd Street		
Postcode/City:	10454	Bronx	
Province/Country:	New York	US-United States of America	
Building type:	Residential		
Climate data set:	US0055c-New York		
Climate zone:	4: Warm-temperate	Altitude of location:	8.2296 m
Home owner / Client:	Breaking Ground		
Street:	505 8th Ave		
Postcode/City:	10018	New York	
Province/Country:	New York	US-United States of America	
Mechanical engineer:	Dagher Engineering		
Street:	29 Broadway		
Postcode/City:	10006	New York	
Province/Country:	New York	US-United States of America	
Certification:	Passive House Academy		
Street:	Wicklow County Campus		
Postcode/City:	A67 X566		
Province/Country:	County Wicklow	IE-Ireland	
Year of construction:	2019	Interior temperature winter [°C]:	20.0
No. of dwelling units:	152	Internal heat gains (IHG) heating case [W/m²]:	4.1
No. of occupants:	174.0	Specific capacity [Wh/K per m² TFA]:	132
		Interior temp. summer [°C]:	25.0
		IHG cooling case [W/m²]:	4.1
		Mechanical cooling:	x

Specific building characteristics with reference to the treated floor area

		7065.3		Alternative criteria		Fulfilled? ²
Space heating	Treated floor area m²			Criteria		
	Heating demand kWh/(m²a)	9	≤	15	-	yes
	Heating load W/m²	12	≤	-	10	
Space cooling	Cooling & dehum. demand kWh/(m²a)	12	≤	18	18	yes
	Cooling load W/m²	10	≤	-	12	
	Frequency of overheating (> 25 °C) %	-	≤	-		-
	Frequency excessively high humidity (> 12 g/kg) %	0	≤	10		yes
	Airtightness	Pressurization test result n ₅₀ 1/h	0.5	≤	0.6	
Non-renewable Primary Energy (PE)	PE demand kWh/(m²a)	119	≤	120		yes
Primary Energy Renewable (PER)	PER demand kWh/(m²a)	87	≤	-	-	-
	Generation of renewable energy (in relation to projected kWh/(m²a) building footprint area)	0	≥	-	-	

² Empty field; Data missing; '-': No requirement

I confirm that the values given herein have been determined following the PHPP methodology and based on the characteristic values of the building. The PHPP calculations are attached to this verification.

Passive House Classic?

yes

Task:	First name:	Surname:
Issued on:	City:	

Signature: