


CERTIFICATE

Certified Passive House Component

Component-ID 0689fx03 valid until 31st December 2017

Passive House Institute
Dr. Wolfgang Feist
64283 Darmstadt
Germany




Category: **Fixed window**
Manufacturer: **Krone Vinduer A/S,
Vra,
Denmark**
Product name: **HeaCO Wood F**

**This certificate was awarded based on the following
criteria for the cool, temperate climate zone**

Comfort $U_W = 0.76 \leq 0.80 \text{ W}/(\text{m}^2 \text{ K})$
 $U_{W,\text{installed}} \leq 0.85 \text{ W}/(\text{m}^2 \text{ K})$
with $U_g = 0.70 \text{ W}/(\text{m}^2 \text{ K})$

Hygiene $f_{Rsi=0.25} \geq 0.70$



cool, temperate climate



**CERTIFIED
COMPONENT**

Passive House Institute

Passive House
efficiency class

phE

phD


phC

phB

phA

phA+

www.passivehouse.com



Description

Timber frame (0,11 W/(m²K)) with insulation (PUR 0,031 W/(m²K)) and external aluminium shell. Pane thickness: 52 mm (6/18/4/18/6), Rebate depth: 13 mm.

Explanation





The window U-values were calculated for the test window size of 1.23 m × 1.48 m with $U_g = 0.70$ W/(m² K). If a higher quality glazing is used, the window U-values will improve as follows:

Glazing	$U_g =$	0.70	0.64	0.58	0.54	W/(m ² K)
		↓	↓	↓	↓	
Window	$U_W =$	0.76	0.71	0.66	0.63	W/(m ² K)




Transparent building components are classified into efficiency classes depending on the heat losses through the opaque part. The frame U-Values, frame widths, thermal bridges at the glazing edge, and the glazing edge lengths are included in these heat losses. A more detailed report of the calculations performed in the context of certification is available from the manufacturer.

The Passive House Institute has defined international component criteria for seven climate zones. In principle, components which have been certified for climate zones with higher requirements may also be used in climates with less stringent requirements. In a particular climate zone it may make sense to use a component of a higher thermal quality which has been certified for a climate zone with more stringent requirements.

Further information relating to certification can be found on www.passivehouse.com and passipedia.org.

Frame values		Frame width b_f mm	U -value frame U_f W/(m ² K)	Ψ -glass edge Ψ_g W/(m K)	Temp. Factor $f_{Rsi=0.25}$ [-]
Top fixed	(tof) 	45	0.64	0.026	0.74
Side fixed	(sf) 	45	0.64	0.026	0.74
Bottom fixed	(bof) 	45	0.64	0.026	0.74
Mullion flying	(fm) 	109	0.82	0.027	0.74
Spacer: SWISSPACER Ultimate			Secondary seal: Polysulfide		

Validated installations

Timber frame		EIFS		Cavity wall (operable)	
					
$\Psi_{install}$	W/(m K)	$\Psi_{install}$	W/(m K)	$\Psi_{install}$	W/(m K)
Top	0.017	Top	0.009	Top	0.017
Side	0.017	Side	0.009	Side	0.017
Bottom	0.025	Bottom	0.012	Bottom	0.019
$U_{W,installed} = 0.82$ W/(m ² K)		$U_{W,installed} = 0.79$ W/(m ² K)		$U_{W,installed} = 0.82$ W/(m ² K)	

