


CERTIFICATE

Certified Passive House Component

Component-ID 0947cw03 valid until 31st December 2017

Passive House Institute
Dr. Wolfgang Feist
64283 Darmstadt
Germany




Category: **Curtain Wall**
Manufacturer: **RP Technik GmbH Profilsysteme,
Bönen,
Germany**
Product name: **RP-tec 50-1 HA**


**This certificate was awarded based on the following
criteria for the cool, temperate climate zone**

Comfort $U_{CW} = 0.80 \leq 0.80 \text{ W}/(\text{m}^2 \text{ K})$
 $U_{CW, \text{installed}} \leq 0.85 \text{ W}/(\text{m}^2 \text{ K})$
with $U_g = 0.70 \text{ W}/(\text{m}^2 \text{ K})$

Hygiene $f_{Rsi=0.25} \geq 0.70$



cool, temperate climate



**CERTIFIED
COMPONENT**

Passive House Institute

Passive House
efficiency class

phE

phD


phC

phB

phA

phA+

www.passivehouse.com



Description

Timber aluminum curtain wall with insulation in the glazing rebate (0.035 W/(mK)) Pane thickness: 44 mm (4/16/4/16/4), rebate depth: 13,5 mm, spacer: SWISSPACER Ultimate.

Explanation






The element U-values were calculated for the test element size of 1.20 m × 2.50 m with $U_g = 0.70 \text{ W}/(\text{m}^2 \text{ K})$. If a higher quality glazing is used, the element U-values will improve as follows:

Glazing	$U_g =$	0.70	0.67	0.63	0.55	W/(m ² K)
		↓	↓	↓	↓	
Element	U_{CW}	0.80	0.77	0.73	0.65	W/(m ² K)

Transparent building components are classified into efficiency classes depending on the heat losses through the opaque part. The frame U-Values, frame widths, thermal bridges at the glazing edge, and the glazing edge lengths are included in these heat losses. A more detailed report of the calculations performed in the context of certification is available from the manufacturer.

The Passive House Institute has defined international component criteria for seven climate zones. In principle, components which have been certified for climate zones with higher requirements may also be used in climates with less stringent requirements. In a particular climate zone it may make sense to use a component of a higher thermal quality which has been certified for a climate zone with more stringent requirements.

Further information relating to certification can be found on www.passivehouse.com and passipedia.org.

Frame values			Frame width b_f mm	U -value frame U_f W/(m ² K)	Ψ -glass edge Ψ_g W/(m K)	Temp. Factor $f_{Rsi=0.25}$ [-]
Top fixed	(tof)		50	1.04	0.028	0.73
Side fixed	(sf)		50	1.04	0.028	0.73
Bottom fixed	(bof)		50	1.04	0.028	0.73
Mullion fixed	(m)		50	1.03	0.030	0.73
Transom fixed	(tf)		50	1.02	0.030	0.73
			Spacer: SWISSPACER Ultimate		Secondary seal: Polysulfide	

Validated installations

