


CERTIFICATE

Certified Passive House Component

Component-ID 0335wi03 valid until 31st December 2020

Passive House Institute
Dr. Wolfgang Feist
64283 Darmstadt
Germany




Category: **Window Frame**
Manufacturer: **Munster Joinery,
Mallow,
Ireland**
Product name: **Passiv AluP+**

**This certificate was awarded based on the following
criteria for the cool, temperate climate zone**

Comfort $U_W = 0.80 \leq 0.80 \text{ W}/(\text{m}^2 \text{ K})$
 $U_{W,\text{installed}} \leq 0.85 \text{ W}/(\text{m}^2 \text{ K})$
with $U_g = 0.70 \text{ W}/(\text{m}^2 \text{ K})$

Hygiene $f_{Rsi=0.25} \geq 0.70$



(Outward opening)

cool, temperate climate



**CERTIFIED
COMPONENT**

Passive House Institute

Passive House
efficiency class

phE


phD

phC

phB

phA

www.passivehouse.com



Calculation model Isothermal

Description

Vinyl frame with insulated cavities with PU-foam (0.028 W/(mK) and interior and exterior aluminium-facing shell . Pane thickness: 52 mm (4/20/4/20/4), Rebate depth: 17 mm.

Explanation





The window U-values were calculated for the test window size of 1.23 m × 1.48 m with $U_g = 0.70 \text{ W}/(\text{m}^2 \text{ K})$. If a higher quality glazing is used, the window U-values will improve as follows:

Glazing	$U_g =$	0.70	0.64	0.58	0.54	W/(m ² K)
		↓	↓	↓	↓	
Window	$U_W =$	0.80	0.76	0.72	0.69	W/(m ² K)

Transparent building components are classified into efficiency classes depending on the heat losses through the opaque part. The frame U-Values, frame widths, thermal bridges at the glazing edge, and the glazing edge lengths are included in these heat losses. A more detailed report of the calculations performed in the context of certification is available from the manufacturer.

The Passive House Institute has defined international component criteria for seven climate zones. In principle, components which have been certified for climate zones with higher requirements may also be used in climates with less stringent requirements. In a particular climate zone it may make sense to use a component of a higher thermal quality which has been certified for a climate zone with more stringent requirements.


Further information relating to certification can be found on www.passivehouse.com and passipedia.org.

Frame values			Frame width b_f mm	U -value frame U_f W/(m ² K)	Ψ -panel edge Ψ_g W/(m K)	Temp. Factor $f_{Rsi=0.25}$ [-]
Top	(to)		102	0.84	0.026	0.74
Side	(s)		102	0.84	0.026	0.74
Bottom	(bo)		102	0.84	0.026	0.74
Mullion 1 casement	(m1)		115	0.84	0.027	0.74
			Spacer: SWISSPACER ULIMATE		Secondary seal: Polysulfid	

Validated installations

EIFS

$U_{Wall} = 0.13 \text{ W}/(\text{m}^2 \text{ K})$




$\Psi_{install}$	W/(m K)
Top	0.009
Side	0.009
Bottom	0.036

$U_{W,installed} = 0.85 \text{ W}/(\text{m}^2 \text{ K})$

Insulated formwork blocks

$U_{Wall} = 0.15 \text{ W}/(\text{m}^2 \text{ K})$




$\Psi_{install}$	W/(m K)
Top	0.001
Side	0.001
Bottom	0.024

$U_{W,installed} = 0.82 \text{ W}/(\text{m}^2 \text{ K})$

Timber frame

$U_{Wall} = 0.13 \text{ W}/(\text{m}^2 \text{ K})$



$\Psi_{install}$	W/(m K)
Top	0.010
Side	0.010
Bottom	0.019

$U_{W,installed} = 0.84 \text{ W}/(\text{m}^2 \text{ K})$

