CERTIFICATE

Certified Passive House Component


ID: 1236cs04 valid until 31. December 2025

Passive House Institute
Dr. Wolfgang Feist
64342 Darmstadt
GERMANY

Aditional thermal bridges

Name Thermal bridge f_{Rsi} Description

Steel bracket X= 0,025 W/K 0,88 Facade mounting bracket



Category Construction system | Steel construction

Manufacturer Knauf Insulation S. L.

Sant Boi de Llobregat

SPAIN

Product name Passivhaus External Wall System

This certificate for the warm, temperate climate zone was awarded based on the following criteria

Hygiene criterion

The minimum temperature factor of the interior surfaces is $\mathbf{f}_{\mathsf{Rsi=0}}$

 $\mathbf{f}_{\text{Rsi}=0,25\text{m}^2\text{K/W}} \ge$ 0,65

Comfort criterion

The U-value of the installed windows is $U_{W,i} \le 1,05 \text{ W}/(\text{m}^2\text{K})$

Efficiency criteria

Heat transfer coefficient of building envelope

Temperature factor of opaque junctions

Thermal bridge-free design for key connection details

Ψ ≤ **0,01** W/(m²K)

f_{Rsi=0,25m²K/W} ≥

U*f_{PHI} ≤

An airtightness concept for all components and connection details was provided

CERTIFIED
COMPONENT
Passive House Institute

0,25 W/(m²K)

0,82

Page 4/4

warm, temperate climate

Phone: | +34 93 379 65 08 | hola@knaufinsulation.com | www.knaufinsulation.es

Opaque building envelope

The Passivhaus External Wall System is a lightweight steel system, designed by Knauf GmbH Sucursal en España, Knauf Insulation S.L., and SIGA, comprising Knauf 100/50 mm steel C-sections and Knauf 48/35 mm steel C-sections filled with Knauf Insulation Ultracoustic 035 (0.035 W/mK) and closed with Knauf Gypsum board between cavities, double Knauf Gypsum board internally and Knauf Aquapanel Outdoor Board externally. The system is further insulated externally with 160mm of Knauf Insulation Naturoll 032 (0,032 W/mK), fixed with steel angles to Knauf Aquapanel Outdoor Board; these also function as fasteners for a rainscreen facade. The system is to be used with a reinforced concrete floor slab, insulated to the underneath with rigid XPS insulation (0,035 W/mK) and internally with Ultracoustic Suelo TP by Knauf Insulation (0,037 W/mK); the roof deck is a flat reinforced concrete slab, insulated to the outside with Knauf Naturoll 032. The system has undergone analysis by the Passive House Institute against the thermal performance criteria for construction systems, and has been deemed suitable for the construction of passive houses in both warm-temperate and warm climates. The ceiling connection does not meet the efficiency criteria of <0,01 W/mK, however this

is typical for such details and, because the hygiene criterion is met, the system has been deemed certifiable.

Windows


Analysis was undertaken using a generic, passive house-standard timber-framed, triple-glazed window unit, featuring phA thermal values for the spacer and a polysulfide secondary seal. The calculations undertaken demonstrate that the window installation locations are suited to the warm-temperate climate zone, with no risk of surface condensation and subsequent mould growth.


Airtightness concept

The airtightness of the construction system is achieved through the use of a SIGA Majrex airtight membrane fitted to the insterior of the steel frame, to the inside of a plasterboard layer. For the junctions between membrane sections and connections to openings and the floor slab, SIGA Sicrall adhesive tape is used.

Explanatory notes

The Passive House Institute has defined international component criteria for seven climate zones based on hygiene, comfort and affordability criteria. In principle, components which have been certified for climate zones with higher requirements may also be used in climates with less stringent requirements. Their use might make economic sense in certain circumstances.





Page 2/4 Passivhaus External Wall System | ID: 1236cs04

Passivhaus External Wall System | ID: 1236cs04

Page 3/4