


CERTIFICATE

Certified Passive House Component

Component-ID 2352rn03 valid until 31st December 2025

Passive House Institute
Dr. Wolfgang Feist
64283 Darmstadt
Germany



Category:

Manufacturer:

Product name:

Construction type:

Main insulation type:

Window product:

Renovation system


**pro Passivhausfenster GmbH,
Oberaudorf,
Germany**

smartshell reno

Light (wood)

Cellulose

smartwin solar HPL



System includes wall and window modules
plus roof modules and floor modules, plus
ventilation, photovoltaics and heat pump



Criteria

1.1 Hygiene criterion:

Lowest interior surface temperature factor above 0.70?

✓

1.2 Airtightness concept:

Comprehensive airtightness concept guide provided?

✓

2.1 Max. heat transfer coefficient:

All U-values below climate zone-specific limit?

✓

2.2 SRI of external finishes:

All solar reflectance indices above limit, where applicable?

N/A

2.3 Absence of thermal bridges:

All Psi-values below limit, or sufficiently reduced?

✓

2.4 Condensation limit:

Condensation evaporated within 12 month period?

✓

2.5 Ma limit:

Moisture accumulation value below limit?

✓

3.1 Window comfort criterion:

Uw-installed value below limit?

✓

3.2 SHGC / g-value of glazing:

g-value of glazing below limit?

✓

3.3 External shading:

External shading strategy for sun-facing windows provided?

✓

4 Ventilation system:

Comprehensive ventilation concept document provided?

✓

5 Installation manual:

Comprehensive installation guide provided?





✓

6 Occupant manual:




Comprehensive use and maintenance guide provided?

✓


Summary of values


Opaque assemblies		U-value $W/(m^2 K)$	Thickness mm
exterior wall	(EW1) 	0.11	802
floor slab	(FS1) 	0.25	320
pitched roof	(RO1) 	0.11	497
pitched roof	(RO2) 	0.10	440

Frame Cuts with "Smartwin Solar HPL" from "pro Passivhausfenster GmbH" (2353wi03)



Frame values		Frame width b_f mm	U-value frame U_f $W/(m^2 K)$	Ψ -glazing edge Ψ_g $W/(m K)$	Temp. Factor $f_{Rsi=0.25}$ [-]
Bottom	(OB1) 	77	0.91	0.026	0.70
Top	(OH1) 	62	0.86	0.026	0.71
Lateral	(OJ1) 	62	0.86	0.026	0.71
Spacer: MULTITECH G			Secondary seal: Polysulfide		



Validated installations



Lightweight timber (operable) 1	
	
ψ_{install}	W/(m K)
Top	0.012
Side	0.016
Bottom	0.025
$U_{W,\text{installed}} = 0.85 \text{ W}/(\text{m}^2 \text{ K})$	



Lightweight timber (operable) 2	
	
ψ_{install}	W/(m K)
Top	0.041
Side	0.023
Bottom	0.025
$U_{W,\text{installed}} = 0.88 \text{ W}/(\text{m}^2 \text{ K})$	












Opaque Assemblies

		Material	Lambda W/(m K)	Thickness (mm)
	exterior wall (EW1) 	Interior plaster Gipsputz 10456	0.570	15
		Existing wall Bestandgebäude	0.650	365
		Lime mortar Putzmörtel aus Kalk	1.000	20
		Smartshell Eq. Smartshell Äq.	0.045	375
		Sto Ventec plaster baseboard Sto Ventec Putzträgerplatte	0.150	12
		Lime mortar Putzmörtel aus Kalk	1.000	15
		Total thickness: 802 mm		
		Rsi: 0.13 m ² K/W		
		Rse: 0.04 m ² K/W		
		U-value: 0.11 W/(m ² K)		




		Material	Lambda W/(m K)	Thickness (mm)
	floor slab (FS1) 	Concrete, 1% Steel Beton, 1% Stahl	2.300	150
		PU foam PU-Schaum	0.027	100
		Cement screed Zement-Estrich	1.400	60
		Artificial stone Kunststein	1.300	10
		Total thickness: 320 mm		
		Rsi: 0.17 m ² K/W		
		Rse: - m ² K/W		
		U-value: 0.25 W/(m ² K)		

 <div>pitched roof (RO1)</div> 	Material	Lambda W/(m K)	Thickness (mm)
	Softwood Weichholz	0.130	100
	Smartshell Eq. Smartshell Äq.	0.045	375
	Softwood Weichholz	0.130	22
	Total thickness: 497 mm		
	Rsi: 0.10 m² K/W		
	Rse: 0.10 m² K/W		
U-value: 0.11 W/(m² K)			

 <div>pitched roof <small>(RO2)</small></div> 	Material	Lambda W/(m K)	Thickness (mm)
	Softwood Weichholz	0.130	20
	Smartshell Eq. Smartshell Äq.	0.052	160
	Softwood Weichholz	0.130	20
	EPS Styropor	0.035	220
	Softwood Weichholz	0.130	20
	Total thickness: 440 mm		
Rsi: 0.10 m² K/W			
Rse: 0.10 m² K/W			
U-value: 0.10 W/(m² K)			

Junctions		U1 U2 W/(m ² K)	Ψ -value Ψ W/(m K)	Temp. factor $f_{Rsi=0.25}$ [-]
Ceiling integration into exterior wall (EW1_EW1_CE_1)		0.11 0.11	0.023	0.974
Ceiling integration into exterior wall (EW1_EW1_CE_2)		0.11 0.11	0.009	0.973
Exterior corner exterior wall (EW1_EW1_ec_1)		0.11 0.11	-0.072	0.930
Interior corner exterior wall (EW1_EW1_ic_1)		0.11 0.11	0.042	0.971
Internal wall integration into exterior wall (EW1_EW1_IW_1)		0.11 0.11	-0.008	0.973
Roof eave pitched roof (EW1_RO1_ea_1)		0.11 0.11	-0.037	0.940
Roof verge pitched roof (EW1_RO1_ve_1)		0.11 0.11	-0.087	0.924
Roof eave pitched roof (EW1_RO2_ea_2)		0.11 0.10	-0.016	0.942
Roof verge pitched roof (EW1_RO2_ve_2)		0.11 0.10	-0.083	0.934
Roof ridge pitched roof (RO1_RO1_ri_1)		0.11 0.11	-0.024	0.928
Roof ridge pitched roof (RO2_RO2_ri_2)		0.10 0.10	-0.033	0.948

Junctions

 <p>Ceiling integration into exterior wall (EW1_EW1_CE_1)</p> <p> $U_{EW1} = 0.11 \text{ W/(m}^2 \text{ K)}$ $U_{EW1} = 0.11 \text{ W/(m}^2 \text{ K)}$ $\Psi = 0.023 \text{ W/(m K)}$ $f_{Rsi} = 0.974$ </p>	 
--	---



Ceiling integration

into exterior wall


(EW1_EW1_CE_2)

$$U_{EW1} = 0.11 \text{ W/(m}^2 \text{ K)}$$

$$U_{EW1} = 0.11 \text{ W/(m}^2 \text{ K)}$$

$$\Psi = 0.009 \text{ W/(m K)}$$

$$f_{Rsi} = 0.973$$



Exterior corner



exterior wall (EW1_EW1_ec_1)

$$U_{EW1} = 0.11 \text{ W/(m}^2 \text{ K)}$$

$$U_{EW1} = 0.11 \text{ W/(m}^2 \text{ K)}$$

$$\Psi = -0.072 \text{ W/(m K)}$$

$$f_{Rsi} = 0.930$$



Interior corner



exterior wall (EW1_EW1_ic_1)

$$U_{EW1} = 0.11 \text{ W/(m}^2 \text{ K)}$$

$$U_{EW1} = 0.11 \text{ W/(m}^2 \text{ K)}$$

$$\Psi = 0.042 \text{ W/(m K)}$$

$$f_{Rsi} = 0.971$$



Internal wall integration



into exterior wall (EW1_EW1_IW_1)

$$U_{EW1} = 0.11 \text{ W/(m}^2 \text{ K)}$$

$$U_{EW1} = 0.11 \text{ W/(m}^2 \text{ K)}$$

$$\Psi = -0.008 \text{ W/(m K)}$$

$$f_{Rsi} = 0.973$$



Roof eave



pitched roof (EW1_RO1_ea_1)

$$U_{EW1} = 0.11 \text{ W/(m}^2 \text{ K)}$$

$$U_{RO1} = 0.11 \text{ W/(m}^2 \text{ K)}$$

$$\Psi = -0.037 \text{ W/(m K)}$$

$$f_{Rsi} = 0.940$$





Roof verge



pitched roof (EW1_RO1_ve_1)

$$U_{EW1} = 0.11 \text{ W/(m}^2 \text{ K)}$$

$$U_{RO1} = 0.11 \text{ W/(m}^2 \text{ K)}$$

$$\Psi = -0.087 \text{ W/(m K)}$$

$$f_{Rsi} = 0.924$$



Roof eave



pitched roof (EW1_RO2_ea_2)

$$U_{EW1} = 0.11 \text{ W/(m}^2 \text{ K)}$$

$$U_{RO2} = 0.10 \text{ W/(m}^2 \text{ K)}$$

$$\Psi = -0.016 \text{ W/(m K)}$$

$$f_{Rsi} = 0.942$$



Roof verge


pitched roof (EW1_RO2_ve_2)

$$U_{EW1} = 0.11 \text{ W/(m}^2 \text{ K)}$$

$$U_{RO2} = 0.10 \text{ W/(m}^2 \text{ K)}$$

$$\Psi = -0.083 \text{ W/(m K)}$$

$$f_{Rsi} = 0.934$$



Roof ridge



pitched roof (RO1_RO1_ri_1)

$$U_{RO1} = 0.11 \text{ W/(m}^2 \text{ K)}$$

$$U_{RO1} = 0.11 \text{ W/(m}^2 \text{ K)}$$

$$\Psi = -0.024 \text{ W/(m K)}$$

$$f_{Rsi} = 0.928$$



Roof ridge



pitched roof (RO2_RO2_ri_2)

$$U_{RO2} = 0.10 \text{ W/(m}^2 \text{ K)}$$

$$U_{RO2} = 0.10 \text{ W/(m}^2 \text{ K)}$$

$$\Psi = -0.033 \text{ W/(m K)}$$

$$f_{Rsi} = 0.948$$



System description

The Smartshell Reno renovation system from Pro Passivhausfenster GmbH is an innovative solution designed for retrofitting existing buildings to enable achievement of the EnerPHit standard. The system comprises pre-fabricated structures with pre-installed Smartwin Solar HPL windows, which are installed over window reveals, fitted in the window production. Prefabricated cassettes constructed from timber Z-profiles are then installed to the walls and roof of the existing building and connected to the window sections using Sto Ventec plaster underlay plates, which are then covered with lime plaster. The resulting cavities are then filled with cellulose insulation (0,040 W/(mK)). The existing floor is insulated with PU foam (0,027 W/ (mK)) and the basement ceiling is also insulated with XPS foam (0,037 W/ (mK)). The airtight layer of the system is created from a layer of lime cement plaster located between the existing structure and the Smartshell Reno system.

Window description

The Smartwin Solar HPL window is a variant of the standard Smartwin Solar window, but rather than an aluminium weather profile to the exterior, a high-pressure laminated (HPL) plate is used. The main window profile is made from spruce/fir (0,11 W/(mK)) and insulated with natural insulation (0,040 W/(mK)). Glass loads are carried by special corner pieces. The airtightness test was conducted on a combination of fixed glazing and tilt and turn sash, element size 2.0 x 2.6 m. Pane thickness: 48 mm (4/18/4/18/4), rebate depth: 15 mm. Spacer: MULTITECH G with polysulfide secondary seal.

Airtightness concept

The Smartshell Reno renovation system enables achievement of the high degree of airtightness required for the EnerPHit standard. In general, this is achieved either by upgrading the external plaster, or by using suitable airtightness membranes and tapes. A full airtightness concept has been provided, and a summary is given in the certification report.

Ventilation concept

The Smartshell Reno renovation system uses the Smartvent heat recovery ventilation system, also manufactured by ProPassivhausfenster GmbH, to enable the level of ventilation required by the EnerPHit standard. A full ventilation concept has been provided, and a summary is given in the certification report.

Heating concept

The Smartshell Reno renovation system uses NIBE heat pump units to provide heating to refurbished dwellings. Depending on the configuration and location of the scheme, the units can take the form of air- or ground-source systems. A full heating concept has been provided, and a summary is given in the certification report.

Additional services

The following services are offered by for the smartshell Reno 2024 system:

Service	Description
Design & consulting	Propassivhausfenster GmbH provides design and consulting services as standard for all projects.
On-site generation	The Smartshell system can be integrated seamlessly with on-site energy generation systems
Quality assurance & monitoring	Pro Passivhausfenster GmbH offers close involvement with all projects, with quality assurance services offered as standard, and ongoing monitoring offered as an additional service.
Heating, DHW and cooling compatibility	Heat pump systems can be seamlessly integrated into the Smartshell Renovation system, offering both heating and cooling.

Disclaimer: The Passive House Institute GmbH (PHI) carries out heat transfer analyses according to the standards set out in the document "[Criteria and Algorithms for Certified Passive House Components: Opaque Construction Systems](#)" and based on information provided by the manufacturer. It is the responsibility of the project leader, e.g. the architect to ensure the appropriate assessments have been carried out for specific buildings, which may include more detailed analyses than those carried out for this certification. Use of a certified Passive House component does not guarantee that a construction project will achieve the [Passive House, EnerPHit or PHI Low Energy Building standard](#). In all cases full details are to be made available by the manufacturer on request to the engaged certified Passive House designer or certifier, who will be permitted to check these against the construction information and to perform on-site checks as part of the quality assurance process.